

X EXTREME VR3



PRODUCT PREVIEW

Full-wet rain tyre, providing exceptional traction and precision on **wet and dirty surfaces**. The directional tread pattern has been developed for the most effective draining of water from the tyre and road contact surface. **The rubber compound in this model has been especially modified** in order to maximize performance in rainy conditions.

TECHNICAL SPECIFICATION

TABLE1: DIMENSIONS

| Tyre Size | Load/Speed Index | Recommended rim width [inch] | Approx. Weight [kg] | Tread Depth [mm] | Overall Diameter [mm] | Tread Width [mm] |
|------------|------------------|------------------------------|---------------------|------------------|-----------------------|------------------|
| 175/50 R13 | 72H | 5.5/6.0/6.5 | - | 6,5 | 504 | 170 |
| 205/60 R13 | 86H | 6.0/6.5/7.0 | 9,9 | 6,5 | 573 | 186 |
| 195/50 R15 | 82H | 6.5/7.0 | 8,7 | 6,5 | 574 | 187 |
| 195/50 R16 | 84H | 6.5/7.0 | - | 6,5 | 600 | 190 |
| 205/45 R17 | 84H | 7.0/7.5 | - | 6,5 | 616 | 195 |
| 225/45 R17 | 91H | 7.5/8.0 | - | 6,5 | 635 | 210 |
| 235/40 R18 | 91H | 7.5/8.0 | - | 6,5 | 650 | 210 |
| 265/35 R18 | 93H | 9.0/9.5/10.0 | - | 6,5 | 631 | 245 |

TABLE2: RUBBER COMPOUNDS

| Version | Hardness | Application | Compound Operating Temperature [°C] | Treadwear Indication |
|-----------|------------|------------------|-------------------------------------|----------------------|
| TYPE - W3 | SUPER SOFT | FULL WET SURFACE | 0 - 30 | - |